

PSH-H 80 Trend

WALL MOUNTED CYLINDER

PRODUCT-NO.: 204772

Comfort meets elegance Wide choice of temperature settings Hot water is something you need many times over throughout the day. It is always available to you with this wall mounted cylinder. This is because the appliance is equipped with an automatic reheating function.

The main features

Electronically controlled wall mounted cylinder

Compact, space saving installation thanks to horizontal design

Very low energy losses thanks to high grade thermal insulation

Long service life thanks to special enamel coating on the inside



PSH-H 30 Trend

Product-No.: 204770



PSH-H 50 Trend

Product-No.: 204771



PSH-H 100 Trend

Product-No.: 204773



PSH-H 120 Trend

Product-No.: 204774



PSH-H 150 Trend

Product-No.: 204775



PSH-H 200 Trend

Product-No.: 204776



| Type | PSH-H 30 Trend | PSH-H 50 Trend | PSH-H 80 Trend |
|----------|----------------|----------------|----------------|
| Part no. | 204770 | 204771 | 204772 |

Technical data

| | | | |
|--|------------|------------|------------|
| Connected load ~ 230 V | 2 kW | 2 kW | 2 kW |
| Rated voltage | 220-240 V | 220-240 V | 220-240 V |
| Load profile | S | M | M |
| Energy efficiency class | C | C | C |
| Standby energy consumption/24 h at 65 °C | 0.78 kWh | 1.09 kWh | 1.04 kWh |
| Nominal capacity | 30 l | 50 l | 80 l |
| Mixed water amount at 40 °C | 46,1 l | 70,5 l | 108 l |
| Temperature setting range | 30-80 °C | 30-80 °C | 30-80 °C |
| Max. flow rate | 23,5 l/min | 23,5 l/min | 23,5 l/min |
| Colour | white | white | white |
| IP rating | IP25 | IP25 | IP25 |
| Height | 412 mm | 412 mm | 517 mm |
| Width | 642 mm | 897 mm | 871 mm |
| Depth | 419 mm | 419 mm | 545 mm |
| Weight | 18.40 kg | 23.40 kg | 31.10 kg |



| Type | PSH-H 100 Trend | PSH-H 120 Trend | PSH-H 150 Trend |
|----------|-----------------|-----------------|-----------------|
| Part no. | 204773 | 204774 | 204775 |

Technical data

| | | | |
|--|------------|------------|------------|
| Connected load ~ 230 V | 2 kW | 2 kW | 2 kW |
| Rated voltage | 220-240 V | 220-240 V | 220-240 V |
| Load profile | M | L | L |
| Energy efficiency class | C | C | C |
| Standby energy consumption/24 h at 65 °C | 1.20 kWh | 1.41 kWh | 1.61 kWh |
| Nominal capacity | 100 l | 120 l | 150 l |
| Mixed water amount at 40 °C | 137,3 l | 128,3 l | 159,4 l |
| Temperature setting range | 30-80 °C | 30-80 °C | 30-80 °C |
| Max. flow rate | 23,5 l/min | 23,5 l/min | 23,5 l/min |
| Colour | white | white | white |
| IP rating | IP25 | IP25 | IP25 |
| Height | 517 mm | 517 mm | 517 mm |
| Width | 1025 mm | 1178 mm | 1410 mm |
| Depth | 545 mm | 545 mm | 545 mm |
| Weight | 35.10 kg | 41.10 kg | 48.40 kg |



| | |
|----------|-----------------|
| Type | PSH-H 200 Trend |
| Part no. | 204776 |

Technical data

| | |
|--|------------|
| Connected load ~ 230 V | 2 kW |
| Rated voltage | 220-240 V |
| Load profile | L |
| Energy efficiency class | C |
| Standby energy consumption/24 h at 65 °C | 1.97 kWh |
| Nominal capacity | 192 l |
| Mixed water amount at 40 °C | 194 l |
| Temperature setting range | 30-80 °C |
| Max. flow rate | 23,5 l/min |
| Colour | white |
| IP rating | IP25 |
| Height | 517 mm |
| Width | 1715 mm |
| Depth | 545 mm |
| Weight | 58.80 kg |

Contact information

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.