

DCE 11/13 H + MEKD

COMPACT INSTANTANEOUS WATER HEATER

PRODUCT-NO.: 205967

This set comprises a compact instantaneous water heater and a pressure-tested mono lever wall mounted tap, providing the perfect combination for kitchen or washroom.

The main features

Optimum complete package for supplying one kitchen sink or one utility sink

Compact instantaneous water heater and special wall mounted tap in one packing unit

For energy efficient and water-saving supply of one hand washbasin

Compact dimensions for unobtrusive integration in the living space



Set-Components 1



Type	DCE 11/13
Product set	DCE 11/13 H + MEKD

Technical data

Rated voltage	400 V
Rated voltage 1	380 V
Rated voltage 2	400 V
Rated voltage 3	415 V
Rated output	11,2/13,5 kW
Rated output 1	10,1/12,2 kW
Rated output 2	11,2/13,5 kW
Rated output 3	12,1/14,5 kW
Rated current	18,7/19,5 A
Rated current 1	17,8/18,5 A
Rated current 2	18,7/19,5 A
Rated current 3	19,4/20,2 A
Fuse protection	16/20 A
Fuse protection 1	16/20 A
Fuse protection 2	16/20 A
Fuse protection 3	20/20 A
Frequency	50/60 Hz
Frequency 1	50/60 Hz

Frequency 2	50/60 Hz
Frequency 3	50/- Hz
Phases	3/PE
Conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} \leq 25$ °C and 380 V)	1111 $\mu\text{S}/\text{cm}$
Conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} \leq 25$ °C and 400 V)	1111 $\mu\text{S}/\text{cm}$
Conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} \leq 25$ °C and 415 V)	1111 $\mu\text{S}/\text{cm}$
Conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} > 25$ °C)	909 $\mu\text{S}/\text{cm}$
Conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} > 25$ °C and 380 V)	909 $\mu\text{S}/\text{cm}$
Conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} > 25$ °C and 400 V)	909 $\mu\text{S}/\text{cm}$
Conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} > 25$ °C and 415 V)	909 $\mu\text{S}/\text{cm}$
Resistivity $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} \leq 25$ °C and 380 V)	900 Ω cm
Resistivity $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} \leq 25$ °C and 400 V)	900 Ω cm
Resistivity $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} \leq 25$ °C and 415 V)	900 Ω cm
Resistivity $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} > 25$ °C)	1100 Ω cm
Resistivity $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} > 25$ °C and 380 V)	1100 Ω cm
Resistivity $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} > 25$ °C and 400 V)	1100 Ω cm
Resistivity $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} > 25$ °C and 415 V)	1100 Ω cm
IP rating	IP24
Temperature setting	20 - 60 °C
Colour	white
Switch-on water flow rate	>2,5 l/min
Height	293 mm
Width	188 mm
Depth	99 mm
Weight	2.10 kg
Energy efficiency class	A

Set-Components **2**

Type	MEKD
Product set	DCE 11/13 H + MEKD

Technical data

Application	Kitchen
Installation type	Wall mounted mixer tap
Surface	chrome plated
Connection	Brass tubes
Cold water connection	1/2 inch
Spout reach	200 mm
Flow rate	13 l/min

Contact information

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.