

VRC-W 450 E Premium

CENTRAL PRODUCT-NO.: 204941

Healthy fresh air with convenience and elegance

Are you looking for a stylish solution to supplying healthy fresh air? Then we recommend this central ventilation unit, which outstrips its predecessor thanks to even greater efficiency, convenience and a modern look. Your qualified contractor can mount the extremely quiet unit on the wall – it is very compact and suitable for ventilating family houses, apartments and small commercial properties.



Make use of numerous functions

Extremely convenient operation of the ventilation unit thanks to self-explanatory control via a matrix display or app. There are numerous functions available, such as seven-day programs, and a choice of eleven languages. But the benefits don't stop with fresh air: thanks to its integral heat exchanger, this model recovers heat energy from the extract air, thus supporting heating. It can also be used for passive cooling.



VRC-W 600 E Premium Product-No.: 204715

The main features

Central, wall mounted ventilation unit for optimum air quality

Best air quality thanks to a choice of filters, including pollen and fine dust filters

WiFi for convenient operation

Easy cleaning and filter change for optimum hygiene

Innovative preheating coil for outdoor air temperature balancing in winter

The programming unit of the ventilation system, which is regulated by CO2 and humidity sensors, can also be used as a remote control

Integrated enthalpy heat exchanger for high humidity recovery

Balanced air flow rate of up to 450 m³/h for efficient operation







| Туре | VRC-W 450 E Premium | VRC-W 600 E Premium |
|----------|------------------------|------------------------|
| Part no. | 204941 | 204715 |

Technical data

| Heat recovery level up to | 77 % | 74.8 % |
|--|---|---|
| Filter class | ePM1 ≥ 50 % (F7) ISO Coarse > 60 % (G4) | ePM1 ≥ 50 % (F7) ISO Coarse ≥ 65 % (G4) |
| Sound power level (EN 12102) | 48,5 dB(A) | 53,7 dB(A) |
| Height | 975 mm | 975 mm |
| Width | 740 mm | 740 mm |
| Depth | 655 mm | 655 mm |
| Air connection diameter | 180 mm | 180 mm |
| WLAN | 802.11b/g/n/ 2.4 GHz/DHCP | 802.11b/g/n/ 2.4 GHz/DHCP |
| Weight | 63 kg | 63 kg |
| Rated voltage | 230 V | 230 V |
| Air flow rate | 110-450 m³/h | 150-600 m³/h |
| Specific energy consumption in moderate climates, time control | -37.07 kWh/(m²a) | -34.99 kWh/(m²a) |
| Specific energy consumption in moderate climates, central demand-dependent control | -38.71 kWh/(m²a) | -36.98 kWh/(m²a |
| Energy efficiency class, moderate climates, time control | А | А |
| Energy efficiency class, moderate climates, central demand- dependent control | А | А |
| Energy efficiency class | A+ | Α |



Contact information

You have questions? We appreciate to help you: Call +49 5531 - 7020 Write an email to info@stiebel-eltron.com

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.